

OVERVIEW

Riverbed® TurboCap is feature-rich Gigabit Ethernet packet capture and injection solution with advanced features such as simultaneous full-rate capture and injection, multi port traffic aggregation, and a configurable pass-thru mode.

Riverbed TurboCap

Feature-rich Gigabit Ethernet Packet Capture and Injection

Riverbed TurboCap is a feature-rich Gigabit Ethernet packet capture and injection solution with advanced features such as simultaneous full-rate capture and injection, multi port traffic aggregation, and a configurable pass-thru mode. Wireshark integration supports packet capture using TurboCap interfaces and off-line analysis of TurboCap capture files. A native TurboCap API and a WinPcap/libpcap API are available for writing/porting your own Gigabit Ethernet applications. TurboCap includes a PCI Express, Dual-Port or Quad-Port, Gigabit Ethernet Board, the TurboCap optimized driver, and a user-level API. TurboCap is available for Windows (XP and Vista) and Linux Fedora 10.

Key Features

- Full-Speed GigE Capture
- Port Aggregation
- Pass-thru Mode
- Aggregating Tap
- Full-Speed GigE Injection
- Exported Interfaces
- TurboCap API Developer's Pack
- Sample applications like "Dump-to-Disk" for high-speed capture to disk




Full-rate Gigabit Ethernet Capture

Full-rate Gigabit Ethernet packet capture is most needed when your network is exhibiting poor performance. There could be many reasons for this including one in which your network is under attack. These are the times when it is important to be able capture traffic from your network without dropping any packets. TurboCap supports full-rate Gigabit capture with even the smallest packet sizes (64 bytes), which is the most challenging situation.

Aggregation of Gigabit Ethernet Traffic Sources

Capturing traffic in timestamp order from two different sources (e.g., a full-duplex link) is a common and important network analysis requirement. This is referred to as "aggregation" and provides a means to measure packet delays between multiple sources, such as the ingress and egress of a switch or router. TurboCap supports full-rate traffic aggregation of the traffic received on pairs of ports of the same board. This is presented to the user as a virtual port called a Board Aggregating Port (BAP).

TurboCap also supports aggregation of ALL of the ports on ALL of the TurboCap boards installed on your system. Specifically, with a single 4-port TurboCap board in a system, you can capture from each of the individual ports, from two, 2-port aggregation ports (ports 0 and 1 and ports 2 and 3), and an aggregation port corresponding to all 4 ports.




Pass-thru Mode

TurboCap can emulate a network tap by being configured to inject the traffic received from one port to the other port on the same board. When the board is in pass-thru mode, the injection is done simultaneously for pairs of ports of the same board and, consequently, TurboCap can act as a Network Tap.

In the figure to the right, the gray blocks along the top edge represent a full duplex link with network traffic flowing in both directions. TurboCap, in pass-thru mode, can be inserted into a full duplex link in such a way that it preserves the traffic along the full duplex link. In the figure, Port A captures the traffic going from left-to-right, injects it back into the full duplex link through Port B, and also passes the captured traffic to user-level applications.

On the other hand, Port B captures the traffic going from right-to-left, injects it back into the full duplex link through Port A, and also passes the captured traffic to user-level applications.



Application Performance

The TurboCap card and optimized driver are capable of capturing full rate Gigabit Ethernet traffic and delivering this data to an application. The overall application performance is often determined by a number of additional factors such as the application's computational tasks, disk write speed, CPU speed, and main memory size. TurboCap is integrated with WinPcap/ libpcap and, consequently, supports applications such as Wireshark, Windump/tcpdump, and Ntop. Note that when using these applications with TurboCap, the capture performance at high data rates will be determined by the specific application. For more information on Wireshark performance in various load scenarios, see <http://wiki.wireshark.org/Performance>.

Full-rate Gigabit Ethernet Traffic Injection

For stress testing your network, TurboCap offers full-rate simultaneous Gigabit Ethernet traffic injection. The TurboCap API is available for developing a wide range of traffic injection applications, e.g. vulnerability testing, etc. Packet sizes can range from 64 bytes to 9234 bytes (jumbo frames) and packets are transmitted in the order they are sent to the driver with minimal delay.

Timestamps

TurboCap offers a range of timestamp modes which trade timestamp accuracy for CPU utilization. You have the option of choosing the timestamp mode that best suits your needs, from highly accurate timestamps to no timestamp generation.

Polling Mode. In this mode, a CPU polls for packet arrivals and timestamps the packet as soon as it is available from the board. These timestamps are very accurate (microsecond accuracy) but require a CPU to be running in a busy wait loop.

Timer Mode. Timer mode uses a 1ms timer to periodically timestamp incoming packets. This puts very little load on the CPU and provides timestamps with millisecond accuracy.

Off. In this case, no timestamps are generated and the timestamp fields in the packet meta-information are set to zero.

Performance and Recommended Hardware


The TurboCap capture board and optimized drivers (Windows and Linux Fedora 10) are only two of the components that determine the overall capture performance of your system. The 2-port TurboCap board requires either a 4-lane or 8-lane PCIe host interface and the 4-port TurboCap board requires an 8-lane PCIe host interface. In order to achieve maximum performance of your TurboCap system, we recommend the following minimum hardware requirements:

PCIe: Either x4 or x8 PCI Express slots depending on the TurboCap board

CPU: Pentium-D (dual core) processor or multiple CPUs (SMP), 2.8GHz

Memory: 2GB RAM

Disk: Full-rate dump-to-disk requires disk arrays that have sufficient capacity and speed to keep up with full-rate Gigabit Ethernet. Disk capacity and speed can be achieved using highly parallel disk arrays.



	TurboCap 2	TurboCap 4
GigE Line-Rate Capture	yes	yes
Wireshark Integration	yes	yes
Full-Rate Traffic Injection	yes	yes
Open API for Development	yes	yes
Port Aggregation	pairwise and ALL ports from all the boards	pairwise and ALL ports from all the boards
Number of Ports	2 ports	4 ports
Host Interface	PCIe 4-lane	PCIe 8-lane



Think fast.®

About Riverbed

Riverbed Technology is the IT performance company. The Riverbed family of wide area network (WAN) optimization solutions liberates businesses from common IT constraints by increasing application performance, enabling consolidation, and providing enterprise-wide network and application visibility – all while eliminating the need to increase bandwidth, storage or servers. Thousands of companies with distributed operations use Riverbed to make their IT infrastructure faster, less expensive and more responsive. Additional information about Riverbed (NASDAQ: RVBD) is available at www.riverbed.com.



2005, 2006, 2007, 2008, 2009



Riverbed Technology
199 Fremont Street
San Francisco, CA 94105
Tel: +1 415 247 8800
Fax: +1 415 247 8801
www.riverbed.com

Riverbed Technology Ltd.
Farley Hall, London Road
Binfield
Bracknell
Berks RG42 4EU
Tel: +44 (0) 1344 401900

Riverbed Technology Pte. Ltd.
391A Orchard Road #22-06/10
Ngee Ann City Tower A
Singapore 238873
Tel: +65 6508-7400

Riverbed Technology K.K.
Shiba-Koen Plaza Building 9F
3-6-9, Shiba, Minato-ku
Tokyo, Japan 105-0014
Tel: +81 3 5419 1990

© 2010 Riverbed Technology, Inc. All rights reserved.
Riverbed and any Riverbed product or service name or logo used herein are trademarks of Riverbed Technology, Inc. All other trademarks used herein belong to their respective owners.